



Technol® STR-2+® Fuel Oil Conditioner

Material Safety Data Sheet I

Section 1. General Information.

NAME: Technol® STR-2+® Fuel Oil Conditioner.

CAS# : N/A

Chem Name : Blend of petroleum distillates

Formula : Proprietary

Molecular Wt. : N/A

Issue Date : August, 1992

Owner : Technol Fuel Conditioners, Inc.

12 Christopher Way

Suite 102

Eatontown, NJ. 07724

Contact : Technol Fuel Conditioners,
Inc.

Telephone : (800) 645-4033

Revised Date : March, 2006

Section 2. Personal Protective Equipment.

Rubber gloves and splashproof goggles are recommended as a standard operation procedure.

Section 3. Hazards Information.

EYES : Irritation of exposed tissue

INGESTION: Irritation of gastrointestinal tract.

SKIN: Irritation of exposed skin due to defatting of skin.

INHALATION: Overexposure will cause dizziness and lack of coordination. Unlikely to occur under normal usage conditions.

BIOLOGICAL : Not Known

FLASH POINT: 126°F Closed Cup

UNUSUAL CHRONIC TOXICITY: Unknown

FLAMMABLE LIMITS IN AIR (%Vol): N/A

UNUSUAL FIRE & EXPLOSIVE HAZARDS:
None Known

PERMISS.CONCENTRATION:
333ppm (Est)

Section 4. Precautions & Procedures.

FIRE EXTINGUISHING TO AVOID: Water

FIRE EXTINGUISHING AGENT RECOMMENDED: Dry Chemical, CO₂, and Chemical Foam.

SPECIAL FIRE FIGHTING PRECAUTIONS: Firefighters should wear self-contained breathing apparatus in the positive mode with full facepiece due to likelihood of fumes, smoke and hazardous decomposition products.

SPECIAL INSTRUCTIONS: Handle as *combustible* petroleum product.

STORAGE: Keep container tightly closed when not needed. Product is pump-able at 10°F but it is recommended to be stored in a warm location and away from extreme heat and sources of ignition. Keep Container upright; do not roll; do not store in plastic - or rubber - or lined containers.

NORMAL HANDLING: Wear rubber gloves and splashproof goggles, particularly if handling large quantities.

VENTILATION: Standard room ventilation should be sufficient in large area; local exhaust recommended for confined areas and at vapor source.

SPILL OR LEAK: Ventilate area. Remove sources of ignition. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Take up small spills with dry chemical absorbent. Large spills may be taken up with pump or vacuum and finished off with dry chemical absorbent. May require extraction of contaminated soil.



Technol® STR-2+® Fuel Oil Conditioner

Material Safety Data Sheet II

Section 5. Physical Characteristics.

ODOR	: Camphor	pH	: N/A
MATERIAL IS	: Liquid	LBS PER GALLON	: 7.60
APPEARANCE	: Blue-Green	SOLUBILITY IN WATER:	Negligible
BOILING POINT	: < 340°F	VAPOR PRESSURE (mm Hg@20°C):	<5
VAPOR DENSITY	: >1	EVAPORATION RATE:	
VOLATILES BY VOLUME	: (@20°C): Nil	(Butyl Acetate=1):	<1
SPECIFIC GRAVITY @25°C (77°F):	0.91		

Section 6. Reactivity Data.

STABILITY	: Product is stable
INCOMPATIBILITY	: Strong oxidizing agents.
CONDITIONS TO AVOID	: Extreme heat and fire
HAZARDOUS POLYMERIZATION	: Will not occur.
HAZARDOUS DECOMPOSITION	: Like all organic compounds and mixtures, extreme heat will generate Carbon Monoxide, Carbon Dioxide and water.

Section 7. First Aid Measures.

INHALATION	: Remove to fresh air - get medical attention.
EYE CONTACT	: Rinse in cool, flowing water for 15 minutes; get medical attention.
SKIN CONTACT:	Wash with soap and water get medical attention if skin irritation persists.
INGESTION:	Get medical attention immediately. DO NOT INDUCE VOMITING; Give Artificial Respiration if breathing stops.

Section 8. Environmental Concerns.

DEGRADABILITY/AQUATIC TOXICITY	: Not Known
RCRA STATUS OF UNUSED MATERIAL	: Dispose in permitted hazardous waste site.
EPA HAZARDOUS SUBSTANCE:	Yes - Reportable Quantity = 100 lbs. for Ignitable substance
WASTE DISPOSAL METHODS:	Incinerate as a waste oil at a registered site; disposer must comply with Federal, State and Local disposal or discharge statutes.

Section 9. References.

GENERAL:	Merck Index, Tenth Edition; Supplied Material Safety Data.
PERMISSIBLE CONCENTRATION REFERENCES:	ACGIH, NIOSH, OSHA; See Registry of Toxic Effects of Chemical Substances for specific test results and the latest regulatory standards.



Technol Fuel Conditioners, Inc.

Distributed by Doctor Diesel

www.doctordiesel.com

(530)524-5020

REV 7/06



Technol® STR-2+®

Fuel Oil Conditioner

Material Safety Data Sheet III

Section 10. Hazardous Ingredients.

This product is a mixture of petroleum derivatives.

This Material is NOT known to contain any Carcinogen listed under OSHA Communication Standard 29 CFR 1910 1200.

NAME	: Aromatic Naphtha	Glycol Ethers
CAS#	: 64742-94-5	111-76-2
APPX % BY WEIGHT	: 60% - 80%	1% to 10%
HAZARD DATE	: N/A	SARA 313

Contains no "Extremely Hazardous Substances (SARA 311/312)"

Section 11. Transportation Information.

EMERGENCY NUMBER: (800) 424-9300 (Chemtrec)

DESCRIPTION: Proprietary mixture of petroleum derivatives.

HANDLE, MARK, LABEL, and TRANSPORT as Combustible Liquid, N.O.S.

DOT HAZARD CLASS: 3. Packing group: III.

UN/NA Number:

NA 1993; Combustible liquid N.O.S., Contains Aromatic Naphtha and Glycol Ethers. Not regulated when shipped in a container less than 120 gallons, by ground within the U.S.

UN 1993; Flammable liquid N.O.S., Contains Aromatic Naphtha and Glycol Ethers. When shipped in a container over 120 gallons, by sea or air, or overseas.

STORE in a cool, dry place between 45°F and 85°F. Keep out of direct sunlight and away from heat sources.

Keep Container upright; do not roll; do not store in plastic - or rubber - lined containers.

Section 12. Additional Information: Disclaimer.

The information contained in the Material Safety Data Sheets have been derived from analysis of published data, publicly available, and supplied component Material Safety Data Sheets. This information and these recommendations are offered in good faith and believed to be correct as of the date hereof. Information and recommendations are supplied upon the condition that the recipients will make their own decision as to safety and suitability for their purposes. While this information is considered accurate, Technol Fuel Conditioners, Inc. makes no warranty, expressed or implied, of merchantability, fitness for a particular purpose, or of any other nature, with respect to the product or information and recommendations regarding this data or the results to be obtained from the use thereof. Technol Fuel Conditioners, Inc. makes no representation as to completeness or accuracy. In no event will Technol Fuel Conditioners, Inc. be responsible for damages of any nature whatsoever resulting from the use or reliance upon the information and recommendations.

Distribution of the Material Safety Data is only one component of your workplace hazard communication program. It is the employer's responsibility to ensure that all employees are properly trained to recognize, evaluate and protect themselves from the risks associated with the storage, use and disposal of this and any other chemical material.